Rock Bolts – Solid Bar

AT Bar

AT

Product – 24mm AT Bolt

Product Code Guide	Bolt Type	Diameter	Length	Drive Nut & Accessories	Coating	Packaging
	AT	4	210	DFP2H	TD	050

Physical Properties

UNDERGROUND

	Minimum		Typical		
Yield Strength	600MPa	200kN	650MPa	240kN	
Tensile Strength	840MPa	305kN	890MPa	340kN	
Calculated Shear Strength	200kN		225kN		
Elongation (After Fracture)	15%		19%		
Mass per Metre	2.97kg				
Bar Core Diameter	Ø21.7mm				
Major Bar Diameter	Ø23.6mm				
Cross Sectional Area	370mm ²				
Rolled Thread	M24 x 3.0mm Pitch				
Impact Toughness			19 Joules		

Key Features

- Manufactured from a special hot rolled deformed bar designed by DSI Underground.
- This bolt features a rib pattern which actively assists with mixing the chemical anchors during installation.
- The AT bolt typically provides marginally higher fracture toughness results over standard AX bar when measured by Charpy Impact Test.
- The deformed rib pattern improves load transfer properties.
- The rolled thread strength nominally equals the column strength of the bar.
- The 24mm chemical anchor bolt is designed to be used with the chemical anchors but can be effectively used with cementitious grouts.
- Corrosion protection may be provided by thermal diffused Obduro coatings.

Installation Guidelines

- 27-28mm hole diameters are preferred.
- Hole depth is critical. Hole depth should be shorter than the bolt to allow for the height of the washer and nut.
- It is important to follow the resin anchor recommended mixing and hold times as printed on the resin anchor cartons.
 Do not over mix.

Length

DSI Underground 25 Pacific Highway NSW 2290 Bennetts Green Australia Phone +61 2 49489099 Fax +61 2 49484087 E-mail sales@dsiunderground.com.au www.dsiunderground.com.au Published Date 06.04.2021

All dimensions, weights, quantities and specifications are those applicable at the time of this publication and may be amended from time to time. Please contact your local DSI Underground representative for final confirmation of any key specifications.



Rock Bolts – Solid Bar

AT Bar

Product Code Prefix



Product – 2<u>4mm AT Bolt</u>

Standard Lengths & Packaging

- Standard bolt lengths range from 600mm to 3000mm in 300mm increments.
- Non-standard requirements are available by negotiation.
- Bolts are packaged in bundles of 50 with sub bundles available on request.
- Bolt fittings, such as nuts, anti-friction washers and domed balls, are supplied fitted to rock bolts in the configuration requested.

Notes

- Only DSI Underground rock bolt components should be used to enable the optimum performance of the bolt system to be obtained
- DSI Underground is Quality Assured to ISO 9001:2015

Typically used products with these items are:



Phone APP

 Want to know more; our full product range, knowledge centre, and other details are available via the App; available on iOS and Android devices by searching "DSI Underground".



DSI Underground 25 Pacific Highway NSW 2290 Bennetts Green Australia Phone +61 2 49489099 Fax +61 2 49484087 E-mail sales@dsiunderground.com.au www.dsiunderground.com.au Published Date 06.04.2021

All dimensions, weights, quantities and specifications are those applicable at the time of this publication and may be amended from time to time. Please contact your local DSI Underground representative for final confirmation of any key specifications.