

Solid Deformed Bar

CS2

Product – Ø20mm Standard Bar

Product Code Guide	Bolt Type	Diameter	Length	Drive Nut & Accessories	Coating	Packaging
	CS	2	210	DFP2H	G	050

Physical Properties

UNDERGROUND

	Minimum		Typical		
Yield Strength	500MPa	150kN	540MPa	160kN	
Tensile Strength	540MPa	160kN	630MPa	190kN	
Calculated Shear Strength	100kN		125kN		
Elongation (After Fracture)	5%		20%		
Mass per Metre	2.46kg				
Bar Core Diameter	Ø19.5mm				
Major Bar Diameter	Ø23mm				
Cross Sectional Area	300mm ²				
Rolled Thread	M20 x 3.0mm Pitch				

Key Features

- The 20mm Solid Deformed Bolt is manufactured from hot rolled reinforcing bar having rib deformations generally in a "herringbone" form.
- The Solid Deformed Bolt features a rib pattern which actively assists with mixing the chemical anchors during installation.
- The deformed rib pattern improves load transfer properties.
- The 20mm solid deformed bolt is usually fully in capsulated with resin but can be effectively used with cementitious grouts or split wedges.
- Corrosion protection may be provided by galvanizing or alternative coatings.

Installation Guidelines

- 26-27mm hole diameters are preferred.
- Hole depth is critical. Hole depth should be shorter than the bolt to allow for the height of the washer and nut.
- It is important to follow the resin anchor recommended mixing and hold times as printed on the resin anchor cartons. Do
 not over mix.

Phone +61 2 49489099
 Fax +61 2 49484087
 E-mail sales@dsiunderground.com.au
 www.dsiunderground.com.au

All dimensions, weights, quantities and specifications are those applicable at the time of this publication and may be amended from time to time. Please contact your local DSI Underground representative for final confirmation of any key specifications.



Rock Bolts – Solid Bar

Solid Deformed Bar

Product Code Prefix

CS₂

Product – Ø20mm Standard Bar

Standard Lengths & Packaging

- Standard bolt lengths range from 600mm to 3000mm in 300mm increments.
- Non-standard requirements are available by negotiation.
- Bolts are packaged in bundles of 50 with sub bundles available on request.
- Bolt fittings, such as nuts, anti-friction washers and domed balls, are supplied fitted to rock bolts in the configuration requested.

Notes

- Only DSI Underground rock bolt components should be used to enable the optimum performance of the bolt system to be obtained
- DSI Underground is Quality Assured to ISO 9001:2015

Typically used products with these items are:



Phone APP

 Want to know more; our full product range, knowledge centre, and other details are available via the App; available on iOS and Android devices by searching "DSI Underground".



DSI Underground 25 Pacific Highway NSW 2290 Bennetts Green Australia Phone +61 2 49489099 Fax +61 2 49484087 E-mail sales@dsiunderground.com.au www.dsiunderground.com.au Published Date 08.06.2021

All dimensions, weights, quantities and specifications are those applicable at the time of this publication and may be amended from time to time. Please contact your local DSI Underground representative for final confirmation of any key specifications.